

Snorkel

INTERNATIONAL



Setting the Standards



Snorkel

Snorkel

INTERNATIONAL

P.O. Box 1160 • St. Joseph, MO 64502-1160
1-800-255-0317 • 1-785-989-3000 • Fax: 785-989-3070
www.snorkelusa.com

Snorkel

INTERNATIONAL



& Reach



Aerial Work Platforms

SETTING THE STANDARDS

Snorkel is one of the most recognized and highly regarded companies in the aerial work platform industry. Our broad product line will increase the efficiency and productivity at construction sites.



As an industry leader, Snorkel has a complete array of support services including service parts, safety training, service schools and trouble shooting guides.

For more information about Snorkel please call **800-255-0317** or **785-989-3000**



Snorkel

INTERNATIONAL

Telescoping and Jib Booms

Articulating Booms

Narrow Slab Scissors

Rough Terrain Scissors

	TB 37	TB 42J	TB 42	TB 47J	TB 50	TB 60	TB 66J	TB 80	TB 85J	TB 100J	TB 120	TB 126J	UNO 414K4	AB 50J	AB 60J	S 1930 (Slab Only)	S 2033 (Slab Only)	S 2646 (Slab Only)	S 3246 (Slab Only)	SR 2584	SR 3284	SR 4084	
Working Height (platform hgt. plus 6 ft.)	43' 13.1 m	48' 14.6 m	48' 14.6 m	53' 16.5 m	56' 17.2 m	66' 20.1 m	72' 21.9 m	86' 26.2 m	91' 27.7 m	106' 32.3 m	126' 38.4 m	132' 40.2 m	46'10" 14.3 m	56' 17.1 m	66' 20.1 m	25' 7.6 m	26' 7.9 m	32' 9.75 m	38' 11.58 m	30'9" 9.4 m	38'4" 11.7 m	45'10" 14.0 m	
Platform Capacity (unrestricted)	600 lbs. 272 kg	500 lbs. 227 kg	500 lbs. 227 kg	500 lbs. 227 kg	500 lbs. 227 kg	500 lbs. 227 kg	500 lbs. 227 kg	500 lbs. 227 kg	500 lbs. 227 kg	600 lbs. 272 kg	500 lbs. 227 kg	500 lbs. 227 kg	500 lbs. 227 kg	500 lbs. 227 kg	500 lbs. 227 kg	500 lbs. 227 kg	800 lbs. 363 kg	1,000 lbs. 454 kg	700 lbs. 318 kg	1750 lbs. 794 kg	1250 lbs. 567 kg	750 lbs. 340 kg	
Platform Size	60"x30" 152x76cm	60"x30" 152x76cm	60"x30" 152x76cm	60"x30" 152x76cm	60"x30" 152x76cm	60"x30" 152x76cm	60"x30" 152x76cm	96"x30" 244x76cm	96"x30" 244x76cm	96"x30" 244x76cm	96"x30" 244x76cm	96"x30" 244x76cm	60"x30" 152x76cm	72"x30" 183x76cm	60"x30" 152x76cm	29"x64" 74x163cm	30"x90" 76x229cm	45"x94" 114.3x238.7cm	45"x94" 114.3x238.7cm	6'x10' 183x305cm	6'x10' 183x305cm	6'x10' 183x305cm	
Horizontal Reach	32' 9.8m	34'9" 10.6m	33' 10.1m	39" 11.9m	39'1" 11.9m	50' 15.2m	56' 17.1m	71'1/2" 21.74m	76'8" 23.4m	66' 20.1m	62' 18.9m	63' 19.2m	23'7 1/2" 7.2m @16'2" 4.9m	28' 8.5m @24' 7.3m	43'1" 13.1m @19'3" 5.9m	3' .9m	3' .9m	NA	NA	4' 1.2m	4' 1.2m	4' 1.2m	
Turntable Rotation	360°cont.	360°cont.	360°cont.	360°cont.	360°cont.	360°cont.	360°cont.	360°cont.	360°cont.	360°cont.	360°cont.	360°cont.	360° non-cont.	360° non-cont.	360° cont.	NA	NA	NA	NA	NA	NA	NA	NA
Power Source	Gas or Diesel	Gas or Diesel	Gas or Diesel	Gas or Diesel	Gas or Diesel	Gas or Diesel	Gas or Diesel	Gas or Diesel	Gas or Diesel	Diesel	Diesel	Diesel	Gas or Diesel	Gas or Diesel	Gas or Diesel	Elec.	Elec.	Elec.	Elec.	Gas or Diesel	Gas or Diesel	Gas or Diesel	
Drive (standard)	2wd	2wd	2wd	2wd	2wd	2wd	2wd	2wd	2wd	2wd	4wd	4wd	4wd	2wd	2wd	2wd	2wd	2wd	2wd	4wd	4wd	4wd	
Drive Speed (maximum-stowed)	3 mph 4.8 kph	3 mph 4.8 kph	3 mph 4.8 kph	3 mph 4.8 kph	3 mph 4.8 kph	3 mph 4.8 kph	3 mph 4.8 kph	3 mph 4.8 kph	3 mph 4.8 kph	3 mph 4.8 kph	3 mph 4.8 kph	3 mph 4.8 kph	4.5 mph 7.2 kph	3.5 mph 5.6 kph	3.5 mph 5.6 kph	1.2 mph 1.9 kph	2.1 mph 3.4 kph	2.0 mph 3.2 kph	2.0 mph 3.2 kph	2.4 mph 3.9 kph	2.4 mph 3.9 kph	2.4 mph 3.9 kph	
Gradeability	25%	25%	25%	25%	25%	25%	25%	25%	25%	25%	25%	25%	30%	25%	20%	20%	20%	25%	25%	40%	37%	32%	
Turning Radius (inside)	5'2" 1.6 m	5'2" 1.6 m	5'2" 1.6 m	5'2" 1.6 m	5'2" 1.6 m	15'5" 4.7 m	15'5" 4.7 m	17'5" 5.3 m	17'5" 5.3 m	17'5" 5.3 m	20' 6.1 m	20' 6.1 m	6'6" 2.0 m	7'5" 2.3 m	8'1/2" 2.4 m	5" 12.7 m	30" 76 m	10" 25.4 cm	10" 25.4 cm	8'6" 2.6 m	8'6" 2.6 m	8'10" 2.7 m	
Overall Height (stowed)	7'6" 2.3 m	7'6" 2.3 m	7'9 1/2" 2.4 m	7'9 1/2" 2.4 m	7'9 1/2" 2.4 m	8'9" 2.7 m	9'1" 2.7 m	9'7" 2.9 m	9'7" 2.9 m	10'4" 3.2 m	10' 3.0 m	10'4" 3.2 m	7'4" 2.3 m	6'11" 2.1 m	8'3" 2.5 m	7'9" 201 cm	7'8 1/2" 199 cm	6'1" 1.5 m	6'7" 1.7 m	7'9 1/4" 2.4 m	8'3 3/4" 2.5 m	8'10 1/4" 2.7 m	
Overall Width (stowed)	7'11 1/2" 2.4 m	7'11 1/2" 2.4 m	7'11 1/2" 2.4 m	7'11 1/2" 2.4 m	7'11 1/2" 2.4 m	8' 2.4 m	8' 2.4 m	8'6" 2.6 m	8'6" 2.6 m	8'6" 2.6 m	8'6" 2.6 m	8'6" 2.6 m	7'2" 2.2 m	7'6" 2.3 m	7' 11 1/2" 2.4 m	30" 76.2 cm	33" 84 cm	46" 1.2 m	46" 1.2 m	7'0" 2.1 m	7'0" 2.1 m	7'0" 2.1 m	
Working Width (minimum)	NA	NA	NA	NA	NA	NA	NA	12'10" 3.9 m	12'10" 3.9 m	12'10" 3.9 m	12'10" 3.9 m	12'10" 3.9 m	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	
Overall Length (stowed)	26'2" 8.0 m	23'9" 7.2 m	23'6" 7.2 m	21'3" 6.5 m	25'1" 7.7 m	30'10" 9.4 m	33' 10.1m	38'10" 11.8m	38'10" 11.8m	44'6" 13.6 m	42'4" 12.9 m	42'9" 13 m	16'3" 5.0 m	21' 6.4 m	29'1 1/2" 8.9 m	66" 168 cm	91" 231 cm	96" 2.4 m	96" 2.4 m	12' 3.7 m	12' 3.7 m	12'6" 3.8 m	
Tire Type	Pneumatic	Pneumatic	Pneumatic	Pneumatic	Pneumatic	Foam Filled	Foam Filled	Foam Filled	Foam Filled	Foam Filled	Foam Filled	Foam Filled	Pneumatic	Pneumatic	Foam Filled	Solid Rubber	Solid Rubber	Solid Rubber	Solid Rubber	Foam Filled	Foam Filled	Foam Filled	
Machine Weight (approx.)	10,500 lbs. 4,763 kg	11,600 lbs. 5,262 kg	10,900 lbs. 4,944 kg	13,500 lbs. 6,123 kg	13,570 lbs. 6,155 kg	21,010 lbs. 9,544 kg	25,000 lbs. 11,340 kg	30,080 lbs. 13,644 kg	30,160 lbs. 13,680 kg	33,000 lbs. 14,969 kg	40,560 lbs. 18,390 kg	42,150 lbs. 19,119 kg	11,200 lbs. 5,080 kg	15,505 lbs. 7,033 kg	23,700 lbs. 10,746 kg	2,950 lbs. 1,336 kg	3,750 lbs. 1,701 kg	5,200 lbs. 2,359 kg	6,620 lbs. 3,003 kg	7,200 lbs. 3,266 kg	8,300 lbs. 3,765 kg	9,300 lbs. 4,218 kg	